# **Brick**com

# 2 Megapixel Day & Night Speed Dome Network Camera

### **OSD-200A 20xp**



#### Sony 2M sensor • HDTV 1080p/720p • WDR Supported

- 2 Megapixel High Resolution Outdoor Speed Dome Camera
- SONY 2M Progressive CMOS sensor
- 20x Optical Zoom, 10x Digital Zoom
- Preset speed Up to 400° /s
- Brickcom WDR Enhancement® Technology inside
- Removable IR-Cut Filter for Day and Night Function
- H.264 HP/MP/BL&MJPEG compression, Quad stream support
- Electronic Image Stabilizer (EIS)
- Privacy Masks for Private Area Protection
- 4sets DI/ 2 sets DO for External Alarm and Sensor Device
- Built-In Micro SD slot/ 802.3at PoE
- Weather-Proof (IP66) Casing with Built-in Fan and Heater





















Onvie

#### **Photo Indication & Dimension Diagram**



- Ethernet LED
   Power LED
   Power
- 4 Factory Reset Button
- 6 Micro SD Card Slot6 Audio I/O
- RJ-45 Connector
- 8 Setting
- Alarm I/O



Camera		Audio	
Hardware System	CPU: 528 MHz Flash: 1GB	Audio Streaming	2-way Audio Support
	RAM: 2GB DDR	Audio Compressio	n G.711 / G.726 ADPCM / AAC
Image Sensor	Sensor Type : 1/2.8" Sony 2 Megapixel Sensor Sensor Resolution : 1920 x 1080 pixel	Audio Input/ Output	Line In/ Out
Minimum Illumination	0.01 lux (F1.6, B/W) 0.05 lux (F1.6, Color)	General	
Lens  Day & Night ICR	SN Ratio: >50dB  20x Optical Zoom Lens Focal Length: f= 4.7 ~ 94 mm F number: F1.6	Operation	Pan: 360°, 0.5°~90°/s Tilt: -10°~190°, 0.5°~90°/s Preset: 256, 5°~400°/s Preset Accuracy: 0.225° Zoom: 20x Optical Zoom
	View Angle: (H): 55°~4°/ (V): 32°~2°/ (D): 62°~5° Removable IR Cut Filter		1~10x variable Digital Zoom Sequence: 8 Auto Pan: 4 Cruise: 8
	Auto Iris/ Auto Focus/ Wide Dynamic Range/ AGC Control/ Backlight Compensation  Triggered by Light sensor, Scheduling,		Privacy Mask: 16 Image Rotation: Flip / Mirror / Inverse / Portrai Auto Flip: Image / Mechanical / Off
Day & Right lor	Digital Input	Communication	Ethernet : one 10/100Mbps RJ-451
Local Storage	Built-in micro SDHC 64GB Memory Card Slot		Supported Protocols: IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTF DHCP, PPPoE, UPnP, IGMP, SNMP, IEEE
Video			802.1x, QoS, ONVIF
Compression Streaming	H.264 / MJPEG Quad Streams H.264*4 / MJPEG + H.264*3	Power Input/ Operating	802.3at PoE (w/o Heater) -7°C ~ 50°C (-19.4°F ~ 122°F)
Video Setting	Auto / Indoor / Outdoor / ATW / Manual White Balance Exposure: Full Auto Mode/ Shutter Priority Mode/ Iris Priority Mode/ Manual Mode	Temperature	AC 24V 3A -40°C ~ 50°C (-40°F ~ 122°F)
Image Resolution	Electronic Shutter: 1/10000~1/1 s  2M (Full HD): 1920x1080	Max. Power Consumption	20Watts (802.3at PoE, w/o Heater) 50Watts (AC 24V 3A)
	SXGA: 1280x1024 XGA:1280x768 1M (HDTV): 1280x720	Environment	Water Proof: IP66 Operating Humidity : 10%~80%
	SVGA: 800x600 D1: 720 x 576 (PAL)/ 720 x 480 (NTSC) VGA: 640x480	Dimension	$\varnothing$ 191.97 $\times$ 282.11 mm ( $\varnothing$ 7.55 $\times$ 11.1 in.) w Sunshield
	CIF: 352 x 288 (PAL)/ 352 x 240 (NTSC)	Weight	2.3 kg (5.11 lb) w/ Sunshield
Frame Rate	<b>2M</b> (Full HD): 1920x1080 @30fps <b>1M</b> (HDTV): 1280x720 @ 30fps	Housing	Weather-proof (IP66)
	D1: 720 x 576 @ 30fps / 720 x 480 @ 30fps CIF: 352 x 288@ 30fps / 352 x 240 @ 30fps	Certification	FCC, CE, IP66
<b>Events and</b>	Alarm Management	Viewing System Requirements	OS: Microsoft Windows 7/Vista/XP/2000 Browser: Internet Explore (6.0+) / Chrome /
Events	Motion Detection/ Alarm Input 4 Sets		Firefox / Safari Quick Time: 6.6 or above VLC
Alarm	Alarm Output 2 Sets Alarm Reaction& Home Function: Preset / Sequence / Auto Pan / Cruise	Warranty	Limited 1-year warranty

#### **Work Best With**

### **Camera Accessories Options**



**72-A1030001 72-A2030001** Power Adapter



D77H07-EPB23 D77H07-EPB13 Power Box



**D77H03-WMP** Mini Pendent



**D77H03-WSP** Pendant



**D77H03-WST2** 50cm Straight Tube



**D77H05-WWBM**Wall Box Mount



**D77H05-WPTB**Pole Box Mount



IP Desktop Joystick



DH801-T Transparent Cover DH801-V Vandal Proof Cover



**DH801-S** Smoke Cover

